


# HP-pålar

H-profil med samma godstjocklek i fläns och liv.

Vägledande kapaciteter

Korrosion,  
knäckning etc  
skall värderas  
särskilt



Profil	Vikt kg / m	Dimension			Stål areal cm <sup>2</sup>	Kapacitet vid S355		Tröghets- moment		Böj- motstånd	
		h mm	b mm	t <sub>w</sub> =t <sub>f</sub> mm		N <sub>d</sub> (γ <sub>m</sub> =1,15) kN	N <sub>t</sub> (f <sub>a</sub> =0,85) kN	x-x cm <sup>4</sup>	y-y cm <sup>4</sup>	x-x cm <sup>3</sup>	y-y cm <sup>3</sup>
HP 220 x 57.2	57.2	210	224.5	11	72,85	2 249	1 912	5 729	2 079	545.6	185.2
HP 260 x 75	75	249	265	12	95,54	2 949	2 507	10 650	3 733	855.1	281.7
HP 260 x 87.3	87.3	253	267	14	111,20	3 433	2 918	12 590	4 455	994.9	333.7
HP 305 x 88	88	301.7	307.2	12,3	111,60	3 445	2 928	18 380	5 949	1 218	387.3
HP 305 x 95	95	303.8	308.3	13,4	121,70	3 757	3 193	20 170	6 552	1 328	425.1
HP 305 x 110	110	307.9	310.3	15,4	140,20	4 328	3 679	23 550	7 680	1 530	495
HP 305 x 126	126	312.4	312.5	17,7	161,60	4 989	4 240	27 540	9 019	1 763	577.2
HP 305 x 149	149	318.5	315.6	20,7	190,00	5 865	4 985	33 050	10 870	2 075	688.8
HP 305 x 180	180	326.7	319.7	24,8	229,30	7 078	6 017	40 970	13 550	2 508	847.4
HP 305 x 186	186	328.3	320.5	25,6	237,00	7 316	6 219	42 580	14 090	2 594	879.3
HP 305 x 223	223	338	325.4	30,5	285,00	8 798	7 478	52 840	17 590	3 127	1 081
HP 320 x 88.5	88.5	303	304	12	112,70	3 479	2 957	18 740	5 634	1 237	370.6
HP 320 x 103	103	307	306	14	131,00	4 044	3 437	22 050	6 704	1 437	438.2
HP 320 x 117	117	311	308	16	149,50	4 615	3 923	25 480	7 815	1 638	507.5
HP 320 x 147	147	319	312	20	186,90	5 770	4 904	32 670	10 160	2 048	651.3
HP 320 x 184	184	329	317	25	234,50	7 239	6 153	42 340	13 330	2 574	841.2
HP 360 x 84.3	84.3	340	367	10	107,30	3 312	2 815	23 190	8 243	1 364	449.2
HP 360 x 109	109	346.4	370.5	12,9	138,90	4 288	3 645	30 620	10 940	1 768	590.7
HP 360 x 133	133	351.9	373.3	15,6	168,50	5 202	4 421	37 730	13 540	2 144	725.3
HP 360 x 152	152	356.4	375.5	17,9	193,80	5 983	5 085	43 950	15 810	2 466	842.3
HP 360 x 174	174	361.5	378.1	20,4	221,70	6 844	5 817	51 020	18 400	2 823	973.5
HP 360 x 180	180	362.9	378.8	21,1	229,30	7 085	6 022	53 040	19 140	2 923	1 011
HP 400 x 122	122	348	390	14	155,90	4 813	4 091	34 770	13 850	1 998	710.3
HP 400 x 140	140	352	392	16	178,60	5 513	4 686	40 270	16 080	2 288	820.2
HP 400 x 158	158	356	394	18	201,40	6 217	5 285	45 940	18 370	2 581	932.4
HP 400 x 176	176	360	396	20	224,30	6 924	5 885	51 770	20 720	2 876	1 047
HP 400 x 194	194	364	398	22	247,50	7 640	6 494	57 760	23 150	3 174	1 163
HP 400 x 213	213	368	400	24	270,70	8 356	7 103	63 920	25 640	3 474	1 282
HP 400 x 231	231	372	402	26	294,20	9 082	7 720	70 260	28 200	3 777	1 403